



CHINA JINWANG ELECTRICAL



24KV-27KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-31	24	100	8000	150	65	530	12	50.5 × 37 × 17
FSC-31	24	200	10000	150	65	530	12	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-34	15	100	10000	110	40	230	7.5	49 × 35 × 11.5
FSC-34	15	200	12000	110	40	230	7.5	



27KV-33KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-32	33	100	6000	170	70	660	15	59 × 36 × 17
FSC-32	33	200	8000	170	70	660	15	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-35	15	100	10000	110	40	230	7.5	49 × 35 × 11.5
FSC-35	15	200	12000	110	40	230	7.5	



36KV-38KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-33	36	100	6000	180	75	850	17	66 × 36 × 17
FSC-33	36	200	8000	180	75	850	17	



15KV-27KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-36	15	100	10000	125	45	230	9.4	55 × 44 × 11.5
FSC-36	15	200	12000	125	45	230	9.4	