



# CHINA JINWANG ELECTRICAL



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-1	15	100	10000	110	40	220	7.3	38.5 x 34.5 x 10.5
FSC-1	15	200	12000	110	40	220	7.3	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-4	15	100	8000	110	40	340	7.5	42 x 33 x 11.5
FSC-4	15	200	10000	110	40	340	7.5	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-2	15	100	10000	110	40	220	7.5	40 x 34.5 x 10.5
FSC-2	15	200	12000	110	40	220	7.5	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-5	15	100	8000	110	40	350	3.5	42 x 35 x 10
FSC-5	15	200	10000	110	40	350	3.5	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-3	15	100	10000	110	40	220	7.3	38.5 x 34.5 x 10.5
FSC-3	15	200	12000	110	40	220	7.3	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-6	15	100	8000	110	40	350	3.8	45 x 35 x 12
FSC-6	15	200	10000	110	40	350	3.8	