



CHINA JINWANG ELECTRICAL



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-7	11	100	6000	110	42	340	8	49 x 27 x 11.5
FSC-7	11	200	8000	110	42	340	8	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-10	15	100	10000	110	45	380	3.5	48.5 x 35 x 10.5
FSC-10	15	200	12000	110	45	380	3.5	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-8	11	100	6000	110	45	530	16.2	62 x 56 x 13.5
FSC-8	11	200	8000	110	45	530	16.2	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-11	15	100	10000	110	40	260	8.5	48.5 x 44 x 13.5
FSC-11	15	200	12000	110	40	260	8.5	



10KV-15KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-9	15	100	10000	110	40	300	7.5	39 x 34.5 x 10.5
FSC-9	15	200	12000	110	40	300	7.5	



15KV-27KV

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-12	15	100	10000	125	45	320	8.5	48.5 x 35 x 10.5
FSC-12	15	200	12000	125	45	350	8.5	