



# CHINA JINWANG ELECTRICAL



**15KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-13	15	100	10000	125	45	320	8.8	51.5 x 34 x 12
FSC-13	15	200	12000	125	45	320	8.8	



**15KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-14	15	100	10000	125	45	320	8.5	47 x 33.5 x 10
FSC-14	15	200	12000	125	45	320	8.5	



**15KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-15	15	100	10000	125	45	320	8.5	48 x 35 x 10.5
FSC-15	15	200	12000	125	45	320	8.5	



**15KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-16	15	100	10000	125	45	320	12	50 x 36 x 13
FSC-16	15	200	12000	125	45	320	12	



**15KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-17	15	100	10000	125	45	320	8.5	48 x 35 x 10.5
FSC-17	15	200	12000	125	45	320	8.5	



**24KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-18	24	100	8000	150	65	530	12	50.5 x 36 x 17
FSC-18	24	200	10000	150	65	530	12	