



# CHINA JINWANG ELECTRICAL



**24KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-19	24	100	6000	150	65	530	12	49 × 37 × 17
FSC-19	24	200	10000	150	65	530	12	



**33KV-36KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-22	36	100	6000	170	70	720	15.5	66 × 37 × 17
FSC-22	36	200	8000	170	70	720	15.5	



**24KV-27KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-20	27	100	6000	150	65	470	13	56 × 38 × 10.5
FSC-20	27	200	10000	150	65	470	13	



**33KV-36KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-23	33	100	6000	170	70	820	28.5	70 × 43 × 17
FSC-23	33	200	8000	170	70	820	28.5	



**27KV-33KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-21	33	100	6000	170	70	660	15	59 × 37 × 17
FSC-21	33	200	8000	170	70	660	15	



**33KV-36KV**

Type	Rated voltage (KV)	Rated current (A)	Breaking current (A)	Impulse voltage (BIL)	Power-frequency withstand voltage	Leakage distance (mm)	Weight (kg)	Dimensions (cm)
FSC-24	38	100	6000	170	70	870	16	98 × 44 × 18
FSC-24	38	200	8000	170	70	870	16	