

## COMPOSITE FUSE CUTOUT



### Product Specifications

Model	Rated Voltage (kV)	Rated Current (A)	Leakage Distance (mm)	Interrupting Current (A)	Power Freq. Withstand Voltage(kV) $\geq$	Impulse Voltage BIL (kV)	Packing Dimension L x W x H (mm)
					Wet		
CFC1-15/100	15	100	330	10000	45	100	400x360x150
CFC1-15/200	15	200	330	12000	45	100	
CFC2-20/100	20	100	420	8000	50	125	500x340x140
CFC2-20/200	20	200	420	10000	50	125	
CFC3-24/100	24	100	580	10000	58	150	490x335x165
CFC3-24/200	24	200	580	12000	58	150	
CFC4-27/100	27	100	620	10000	60	150	500x360x140
CFC4-27/200	27	200	620	12000	60	150	
CFC5-33/100	33	100	730	8000	65	165	520x325x150
CFC5-33/200	33	200	730	10000	65	165	
CFC6-36/100	36	100	960	8000	70	170	660x360x140
CFC6-36/200	36	200	960	10000	70	170	

Note 1: OEM Drawings of Cutout Insulators can be met separately.

Note 2: Mounting Bracket & different Cutout Fittings can be supplied according to requirements.